

## NK42E0H-1T(WD) PoE Kit

### Key Feature

- H.265+/H.265/H.264+/H.264 video compression
- PoE connection
- 4 × 2 MP IR fixed network bullet camera
- 1 x NVR, full channel recording at up to 4 MP resolution



### Camera

- 1/2.8" Progressive Scan CMOS
- 1920 × 1280@30 fps
- 2.8 mm fixed lens
- Color: 0.01 Lux @(F1.2; AGC ON), 0.028 Lux @(F2.0; AGC ON)
- 3D Digital Noise Reduction

### NVR

- Up to 4-ch network camera inputs (up to 4 MP)
- 2-ch@1080p/1-ch@4 MP decoding capability
- HDMI/VGA output with up to 1920 × 1080 resolution
- Hik-Connect for easy network management




## Specification

<b>Kit Model</b>	NK42E0H-1T(WD)
<b>Camera Model</b>	4 × DS-2CD1023G0E-I
<b>NVR Model</b>	DS-7104NI-Q1/4P/M(1T)
<b>Camera</b>	
<b>Image Sensor</b>	1/2.8" Progressive Scan CMOS
<b>Min. Illumination</b>	Color: 0.01 Lux @(F1.2; AGC ON), 0.028 Lux @(F2.0; AGC ON)
<b>Shutter Speed</b>	1/3 s to 1/100,000 s
<b>Day &amp; Night</b>	IR cut filter
<b>WDR</b>	DWDR
<b>Angle Adjustment</b>	Pan: 0° to 360°, tilt: 0° to 180°, rotation: 0° to 360°
<b>Protection Level</b>	IP67
<b>Material</b>	Front cover: metal, back cover & bracket: plastic
<b>Lens</b>	
<b>Focal Length</b>	2.8 mm
<b>Aperture</b>	F2.0
<b>Focus</b>	Fixed
<b>FOV</b>	Horizontal FOV: 114.8°, vertical FOV: 62°, diagonal FOV: 135.5°
<b>Lens Mount</b>	M12
<b>IR</b>	
<b>IR Range</b>	Up to 30 m
<b>Compression Standard</b>	
<b>Video Compression</b>	Main stream: H.265+/H.265/H.264 +/H.264 Sub-stream: H.265/H.264/MJPEG
<b>H.264 Type</b>	Main Profile/High Profile/Baseline Profile
<b>H.264+</b>	Main Profile
<b>H.265 Type</b>	Main Profile
<b>H.265+</b>	Main Profile
<b>Video Bit Rate</b>	32 Kbps to 8 Mbps
<b>Image</b>	
<b>Max. Resolution</b>	1920 × 1080
<b>Main Stream</b>	50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720)
<b>Sub-stream</b>	50 Hz: 25 fps (640 × 480, 640 × 360, 320 × 240) 60 Hz: 30 fps (640 × 480, 640 × 360, 320 × 240)
<b>Image Setting</b>	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
<b>Day/Night Switch</b>	Auto/Scheduled/Day/Night
<b>Network</b>	
<b>Alarm Trigger</b>	Motion detection, video tampering alarm, illegal login
<b>Protocols</b>	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
<b>General Function</b>	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
<b>Client</b>	iVMS-4200, Hik-Connect, iVMS-5200, iVMS-4500
<b>Interface</b>	
<b>Communication Interface</b>	1 RJ45 10M/100M self-adaptive Ethernet port

Video Out	No
Alarm I/O	No
Reset Button	No
<b>General</b>	
Power Supply	12 VDC $\pm$ 25%, $\Phi$ 5.5 mm coaxial plug power, or PoE (802.3af, class 3)
Consumption	12 VDC, 0.3 A, Max: 3.5 W, or PoE (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 4.5 W
Working Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working Humidity	95% or less (non-condensing)
Dimension (W $\times$ D $\times$ H)	$\Phi$ 70 mm $\times$ 172.7mm (2.8" $\times$ 6.8")
Weight	Approx. 270 g (0.6 lb)
<b>General</b>	
Power Supply	12 VDC $\pm$ 25%, $\Phi$ 5.5 mm coaxial plug power, or PoE (802.3af, class 3)
Consumption	12 VDC, 0.3 A, Max: 3.5 W, or PoE (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 4.5 W
Working Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working Humidity	95% or less (non-condensing)
Dimension (W $\times$ D $\times$ H)	$\Phi$ 70 mm $\times$ 172.7mm (2.8" $\times$ 6.8")
Weight	Approx. 270 g (0.6 lb)
<b>NVR</b>	
<b>Video and Audio</b>	
IP Video Input	4-ch
	Up to 4 MP resolution
Incoming/Outgoing Bandwidth	40 Mbps/60 Mbps
HDMI/VGA Output	1920 $\times$ 1080/60Hz, 1280 $\times$ 1024/60Hz, 1280 $\times$ 720/60Hz, 1024 $\times$ 768/60Hz
<b>Decoding</b>	
Decoding Format	H.265+/H.265/ H.264+/H.264
Video Resolution	4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	4-ch
Capability	2-ch@1080p / 1-ch@4 MP
<b>Network</b>	
Network Interface	1, RJ45 10/100M Ethernet interface
Network Protocol	IPv6, UPnP™, NTP, SADP, DHCP
Remote Connection	16
<b>PoE</b>	
Interface	4, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	$\leq$ 36 W
Standard	IEEE 802.3 af/at
<b>Auxiliary interface</b>	
SATA	1 SATA interface
Capacity	Up to 6 TB capacity for each disk
USB Interface	Rear panel: 2 $\times$ USB 2.0
Alarm In/Out	No
<b>General</b>	

<b>Power Supply</b>	48 VDC
<b>Consumption (without HDD and PoE off)</b>	≤ 10 W
<b>Working Temperature</b>	-10 °C to 55 °C (14 °F to 131 °F)
<b>Working Humidity</b>	10% to 90%
<b>Dimension (W × D × H)</b>	265 × 225 × 48 mm (10.4" × 8.9" × 1.9")
<b>Weight (without hard disk)</b>	≤ 1 kg (2.2 lb)
<b>Kit</b>	
<b>Accessories</b>	Power: 1 power cable Network cable: 4 × 18.3 m (60 ft) video and power cable HDMI cable: 1 HDMI cable
<b>Hard Drive</b>	Pre-installed 1 TB HDD
<b>Certification</b>	FCC, CE
<b>Weight (with package)</b>	≤ 8 kg (17.6 lb)

### Camera Dimension




### Accessory




DS-1280ZJ-XS  
Junction Box

# NVR Dimension



Unit: mm

## Physical Interface



No.	Description	No.	Description
1	Power Supply	5	LAN Network Interface
2	VGA Interface	6	Network Interfaces with PoE function
3	HDMI Interface	7	Ground
4	USB Interface		

## Available Model

NK42E0H-1T(WD)

Distributed by:



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6890  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 [216]521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652 2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (11) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6884-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-0131-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com