

DS-2TS16-35VI/W**Handheld Thermal & Optical Bi-spectrum Binocular**

Hikvision DS-2TS16-35VI/W Handheld Thermal & Optical Bi-spectrum Binocular is equipped with ultra-low light optical detector, 640 × 512 @25fps thermal detector, 1280 × 960 @25fps OLED display and eyepiece with large field of view. The device can quickly discover and locate hiding objects even under extreme environment, such as smoke, fog, rain and snow. It can be widely applied to scenarios like patrol, law enforcement, search and rescue, drug enforcement, anti-smuggling and suspect capture.

Key Features

- Thermal: 640 × 512 @25fps, optical: 1280 × 960 @25fps
- Adaptive AGC, DDE, 3D DNR, NETD less than 40 mk (25°C, F#=1.0)
- Ultra-low illumination (optical channel), B/W: 0.001 lux @ (F1.0 , AGC On)
- 0.39-inch OLED display
- Automatic OLED backlight
- Manual focus for thermal lens
- Bi-spectrum image fusion and object highlight (detail enhancement and target recognition)
- Video recording, replay, picture snapshot and search (capable to review the event on device)
- Wi-Fi hot spot, GPS, cursor display

www.hikvision.com

Specification

Thermal Module	
Image Sensor	Uncooled Focal Plane Arrays
Max. Resolution	640 × 512 @25fps
Pixel Interval	17µm
Response Waveband	8µm to 14µm
NETD	less than 40 mK (25°C, F#=1.0)
Lens (Focal Length)	35 mm, Manual Focus, Electric focus
MRAD	0.486 mrad
Field of View	17.7° × 14.2° (H × V)
Digital Zoom	4×
Aperture	F1.0
Optical Module	
Max. Image Resolution	1280 × 960 @25fps
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	B/W : 0.001 lux @ (F1.0 , AGC On)
Lens (Focal Length)	12 mm
Image Enhancement	3D DNR, Adaptive AGC
Image Display	
Monitor	0.39-inch, OLED, 1024 × 768
Thermal/Optical Mode	Thermal view, B/W optical view, image fusion view are selectable
Image Fusion	Color fusion, B/W fusion
Pallets	Black hot, white hot
Smart Function	
Hot Track	Yes
Object Highlight	Yes
Automatic Backlight	The OLED backlight automatically turns off if no human eyes are detected.
Cursor Display	A cursor shows in the view for roughly measuring distance from the target.
System	
Storage	Built-in memory module (32GB)
Record Video	On-board video recording
Snapshot	On-board image capturing
Video Replay	Yes
Picture Search	Yes
Wi-Fi	Yes
GPS	Yes

Power Supply	
Battery Type	Four 18650 batteries, requires 5 hours to be fully charged
Battery Operating Time	More than 7 hours
Battery Capacity Display	Yes
General	
Menu language	English
Power	DC 5V/2A
Working Temperature	-30 °C to 55 °C (-22 °F to 131 °F)
Protection Level	IP67
Mounting	UNC 1/4"-20
Cable Output	Aviation plug: connecting to BNC, DB9, and USB
Accessories (Supplied)	Battery charger, battery charger power cable, wiping cloth, two wrist straps, User manual, aviation plug cable, eight batteries
Dimension	164mm × 182.3mm × 73.3mm (6.46" × 7.18" × 2.89")
Weight	Less than 1.0 Kg (2.20 lb)

Detection Range Table

* The table is only for reference, the performance may vary from camera to camera.

Wide Range Coverage


There is range limit for detecting, recognizing, and identifying human/vehicle targets.

Detection Range (Vehicles: 1.4×4.0m)	Detection Range (Humans: 1.8×0.5m)	Recognition Range (Vehicles: 1.4×4.0m)	Recognition Range (Humans: 1.8×0.5m)	Identification Range (Vehicles: 1.4×4.0m)	Identification Range (Humans: 1.8×0.5m)
3157 m	1029 m	789 m	257 m	395 m	129 m

Available Model

DS-2TS16-35VI/W

Dimension



Distributed by

HIKVISION**Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA

T +1-809-895-0400

sales.usa@hikvision.com

Hikvision Australia

T +61-2-8599-4233

salesau@hikvision.com

Hikvision India

T +91-22-28469900

sales@pramahikvision.com

Hikvision Canada

T +1-866-200-6890

sales.canada@hikvision.com

Hikvision Thailand

T +662-275-9949

sales.thailand@hikvision.com

Hikvision Europe

T +31-23-5542770

sales.eu@hikvision.com

Hikvision Italy

T +39-0438-6902

info.it@hikvision.com

Hikvision Brazil

T +55 11 3318-0050

Latam.support@hikvision.com

Hikvision Turkey

T +90 (216)521 7070- 7074

sales.tr@hikvision.com

Hikvision Malaysia

T +601-7852-2413

sales.my@hikvision.com

Hikvision UK & Ireland

T +01628-902140

sales.uk@hikvision.com

Hikvision South Africa

Tel: +27 (10) 0351172

sale.africa@hikvision.com

Hikvision France

T +33(0)1-85-330-450

info.fr@hikvision.com

Hikvision Kazakhstan

T +7-727-9730667

nikia.panfilov@hikvision.ru

Hikvision Vietnam

T +84-974270888

sales.vt@hikvision.com

Hikvision UAE

T +971-4-4432090

salesme@hikvision.com

Hikvision Singapore

T +65-6684-4718

sg@hikvision.com

Hikvision Spain

T +34-91-737-16-55

info.es@hikvision.com

Hikvision Tashkent

T +99-87-1238-8438

uzb@hikvision.ru

Hikvision Hong Kong

T +852-2151-1761

info.hk@hikvision.com

Hikvision Russia

T +7-495-669-67-99

salesru@hikvision.com

Hikvision Korea

T +82-(0)31-731-8817

sales.korea@hikvision.com

Hikvision Poland

T +48-22-460-01-50

info.pl@hikvision.com

Hikvision Indonesia

T +62-21-2933759

Sales.Indonesia@hikvision.com

Hikvision Colombia

Sales.colombia@hikvision.com