


## PN-Series LCD Display 55"



### Ultra Narrow Bezel Displays for Immersive Visual Experience

The PN-Series ultra-narrow bezel displays are designed for professional and commercial video wall applications. Given its built-in scheduler, OPS slot, and tiling function, these high-end displays are easy to set up and maintain. With its up to 500 nits of brightness, anti-reflective panel, visually stunning video walls can be displayed in demanding environments — from large public venues to 24/7 operation control rooms.






### Immersive Visual Experience

55" ultra-narrow 3.5 mm bezel-to-bezel professional video wall displays create seamless images for an immersive visual experience, while the flexible landscape or portrait display orientation suits favorable content layouts and fulfills different applications.


### High Visibility and Low Power Consumption

Anti-glare treatment with haze 28%, high contrast, wide viewing angles and up to 500 nits brightness give images with superior clarity and visibility. EcoSmart sensor detects ambient lighting conditions to automatically adjust the brightness level and reduce power consumption.



### DisplayPort Daisy-chain for 4K Video Wall Installation

With DisplayPort daisy chain functionality, the video and audio can be delivered to multiple AG Neovo's large format displays using DisplayPort cables to set up, configure and maintain 2x2 4K video wall installations with ease.




### Easy Control for Multiple Displays

With IR/RS232/LAN loop-through capability, the PN-Series provides an easy and convenient single point of control for multi-display installation.

### Versatile connectivity for Multimedia Playback

The PN-Series integrates diverse connectivity, including HDMI, DisplayPort, DVI, VGA and OPS slot to connect external devices. In addition, the displays support USB playback functionality and users can directly playback multimedia content via LAN connection.



### Simple Content Scheduling

The built-in scheduler allows users to conveniently play content from a USB drive. Users can simply create scheduled playlists and configure playback settings with the included remote control to display personalised content.



## Industry-leading Durability

Designed for 24/7 operation, these durable metal-cased displays take advantage of superior components to ensure a long product lifetime. Its integrated HeatControl Sensor automatically activates the internal cooling fans, which is crucial when the temperature rises in mission-critical installations.

## Free Display Management Software

PID Command & Ctrl software allows users to control AG Neovo displays via laptop or mobile devices remotely. It provides a simple and intuitive interface for remote management, OSD-related settings, and easy control of deployed displays and video walls. The embedded UniWall™ feature allows AG Neovo displays to create up to 5x5 video walls without third-party equipment.

The software also has functions like brightness adjustment, temperature, and usage time monitoring for reliable maintenance.



## Features

- Full HD 1920 x 1080 resolution
- IPS Panel technology offers high colour accuracy and wide viewing angles
- Anti-glare treatment (Haze 28%) improves visibility of the screen under ambient light
- 3.5mm ultra narrow bezel for seamless LCD video walls (1.75 mm bezel width per unit)
- DisplayPort, DVI, RS232, LAN, IR looping support
- 500 nits of brightness for any indoors and semi-outdoor environments
- Anti-Burn-in™ technology prevents image ghosting
- Versatile connectivity: DisplayPort, HDMI, DVI, VGA, Component/Composite
- Flexible display orientation: Landscape/Portrait
- An integrated scheduler allows content programming based on time and day
- Extensive display control: RS232, RJ45 and PID Command Tool software
- UniWall™ - create video walls (up to 5x5 displays) without third-party equipment
- Designed and developed for continuous 24/7 operation
- HeatControl Sensors automatically activate the internal cooling fans when temperature rises
- Selectable gamma curves optimise different kinds of images

**Specifications**
**PN-55D2**
**Panel**

Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	54.6"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.630 mm
Brightness	500 cd/m²
Contrast Ratio	1200:1
Viewing Angle (H/V)	178°/178°
Display Colour	1.07B
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 28%), 2H Hard Coating

**Frequency**

Frequency (H)	31 kHz-92 kHz
Frequency (V)	48 Hz-85 Hz

**Signal Input**

DisplayPort	1.2 x 1
HDMI	1.3b x 2
DVI	24-Pin DVI-D
VGA	15-Pin D-Sub x 1
Component	BNC x 1
Composite	BNC x 1 (Share with Component-Y)

**Signal Output**

DisplayPort	1.2 x 1
DVI	29-Pin DVI-I x 1 (VGA/DVI/HDMI/OPS)

**External Control**

IR In	3.5 mm Phone Jack
IR Out	3.5 mm Phone Jack
RS232 In	2.5 mm Phone Jack
RS232 Out	2.5 mm Phone Jack
LAN	RJ45 x 2

**Other Connectivity**

USB	2.0 x 1 (Service Port / Media Playback)
OPS Slot	Yes

**Audio**

Audio In	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
Audio Out	Stereo Audio Jack (3.5 mm)
Internal Speakers	10W x 2
Speaker Output (RMS)	10W x 2

**Power**

Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	100W (On)
Standby Mode	< 0.5W
Off Mode	0W

**Operating Conditions**

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)

**Storage Conditions**

Temperature	-20°C-60°C (-4°F-140°F)
Humidity	5%-90% (non-condensing)

**Mounting**

VESA FPM PMI	Yes (400 x 400 mm)
--------------	--------------------

**Security**

Kensington Security Slot	Yes
--------------------------	-----

**Dimensions**

Product w/o Base (W x H x D)	1213.4 x 684.2 x 99.55 mm (47.8" x 26.9" x 3.9")
Packaging (W x H x D)	1395.0 x 848.0 x 280.0 mm (47.8" x 33.4" x 11.0")

**Weight**

Product w/o Base	24.4 kg (53.8 lb)
Packaging	32.7 kg (72.1 lb)

**Regulation Approval**

Certifications & Compliance	CE, CB, FCC, WEEE, RoHS, REACH
-----------------------------	--------------------------------

**Accessories**

Supplied	Power Cord, HDMI Cable, RS232 Cable, Remote Control, Batteries, RS232 Daisy Chain Cable, IR Sensor, Quick Start Guide
----------	---

**Optional Accessories**

Floor Mount	FMS-01, FMS-02, FMC-02
Floor Mount (Landscape only)	FMC-03+LMK-04, FMC-04+LMK-04
Ceiling Mount (Landscape only)	CMP-01+LMK-01
Video Wall Mount	VWM-01, VWM-02
Wall Mount	LMA-01
Wall Mount (Landscape only)	LMK-01, LMK-03
Desk mount (Landscape only)	DTS-01
Stand	STD-05

All specifications are subject to change without prior notice.

Copyright © 2021 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.

All other trademarks are the property of their respective owners.

P/C: PN5D20 Version 1.0, 20210408



Google Play is a trademark of Google, Inc.

[www.agneovo.com](http://www.agneovo.com)

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Støvring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[www.agneovo.com](http://www.agneovo.com)