

DS-2CD3126G2-IS

AcuSense 2 MP IR Fixed Dome Network Camera



Empowered by deep learning algorithms, Hikvision AcuSense technology brings human or vehicle target classification alarms to front- and back-end devices. The system can greatly reduce false alarms generated by targets other than humans or vehicles, vastly improving alarm efficiency and effectiveness.

- High quality imaging with 1080p @60 fps
- Excellent low-light performance with powered-by-DarkFighter technology
- Efficient H.265+ compression technology
- Clear imaging against strong back light due to 120 dB true WDR technology
- False alarm reduction through human and vehicle target classification based on deep learning
- Advanced streaming technology that enables smooth live view and data self-correcting in poor network
- Water and dust resistant (IP67) and vandal-resistant (IK10)



▪ Specification

| Camera | |
|-----------------------------|---|
| Image Sensor | 1/2.8" Progressive Scan CMOS |
| Min. Illumination | 0.002 Lux @ (F1.4, AGC ON) |
| Shutter Speed | 1/3 s to 1/100,000 s |
| Slow Shutter | Yes |
| P/N | P/N |
| Wide Dynamic Range | 120 dB |
| Day & Night | ICR Cut |
| Angle Adjustment | Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355° |
| Lens | |
| Lens Mount | M12 |
| Lens Type & FOV | 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 129° 4 mm, horizontal FOV 86°, vertical FOV 47°, diagonal FOV 102° 6 mm, horizontal FOV 55°, vertical FOV 29°, diagonal FOV 65° |
| Aperture | F1.4 |
| Illuminator | |
| IR Range | Up to 40 m |
| Wavelength | 850 nm |
| Smart Supplement Light | Yes |
| Video | |
| Max. Resolution | 1920 × 1080 |
| Main Stream | 50Hz: up to 50 fps (1920 × 1080, 1280 × 720) 60Hz: up to 60 fps (1920 × 1080, 1280 × 720) *High frame rate is supported under certain settings. |
| Sub-Stream | 50Hz: 25 fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30 fps (640 × 480, 640 × 360, 320 × 240) |
| Third Stream | 50Hz: 15 fps (1280 × 720, 640 × 480, 640 × 360, 320 × 240) 60Hz: 15 fps (1280 × 720, 640 × 480, 640 × 360, 320 × 240) |
| Fourth Stream | 50Hz: 15 fps (1280 × 720, 640 × 480, 640 × 360, 320 × 240) 60Hz: 15 fps (1280 × 720, 640 × 480, 640 × 360, 320 × 240) *Fourth stream is supported under certain settings. |
| Video Compression | Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264 Fourth stream: H.265/H.264/MJPEG *Fourth stream is supported under certain settings. |
| Video Bit Rate | 32 Kbps to 8 Mbps |
| H.264 Type | Baseline Profile/Main Profile/High Profile |
| H.265 Type | Main Profile |
| H.264+ | Main stream supports |
| H.265+ | Main stream supports |
| Bit Rate Control | CBR/VBR |
| Scalable Video Coding (SVC) | Yes |
| Region of Interest (ROI) | 5 fixed regions for main stream and sub-stream |


| Audio | |
|--|--|
| Environment Noise Filtering | Yes |
| Audio Sampling Rate | 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz |
| Audio Compression | G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3 |
| Audio Bit Rate | 64Kbps(G.711ulaw/G.711alaw)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)/8-320Kbps(MP3) |
| Network | |
| Simultaneous Live View | Up to 6 channels |
| API | Open Network Video Interface (PROFILE S, PROFILE G), ISAPI, SDK |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, PPPoE |
| User/Host | Up to 32 users. 3 user levels: administrator, operator and user |
| Security | Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.2, WSSE and digest authentication for Open Network Video Interface |
| Network Storage | MicroSD/SDHC/SDXC card (256 GB) local storage, and NAS(NFS, SMB/CIFS), auto network replenishment (ANR) |
| Client | iVMS-4200, Hik-Connect, Hik-Central |
| Web Browser | Plug-in required live view: IE 10, IE 11 Plug-in free live view : Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+ |
| Image | |
| Day/Night Switch | Day, Night, Auto, Schedule |
| Target Cropping | Yes |
| Image Enhancement | BLC, HLC, 3D DNR |
| Image Parameters Switch | Yes |
| Image Settings | Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser |
| Interface | |
| Alarm | 1 input, 1 output (max. 12 VDC, 30 mA) |
| Audio | 1 input (line in), max. input amplitude: 3.3 vpp, input impedance:4.7 K Ω , interface type: non-equilibrium; 1 output (line out), max.output amplitude: 2.5 vpp, output impedance: 100 Ω , interface type: non-equilibrium, mono sound |
| On-board Storage | Built-in micro SD/SDHC/SDXC slot, up to 256 GB |
| Hardware Reset | Yes |
| Communication Interface | 1 RJ45 10M/100M self-adaptive Ethernet port |
| Power Output | 12 VDC, max. 100 mA (supported by all power supply types) |
| Smart Feature-Set | |
| Basic Event | Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error), scene change detection |
| Intelligent (Deep Learning Algorithm) | |
| Face Capture | Yes |
| Premier Protection | Line crossing detection, intrusion detection, region entrance detection, region exiting detection |
| General | |
| Linkage Method | Upload to NAS/memory card, notify surveillance center, trigger record, trigger capture |

| | |
|----------------------------------|---|
| Web Client Language | 33 languages English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| General Function | Anti-flicker, heartbeat, mirror, privacy masks, flash log, password reset via e-mail, pixel counter |
| Software Reset | Yes |
| Storage Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing) |
| Startup and Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing) |
| Power Supply | 12 VDC ± 25%, 9 to 15 VDC, two-core terminal block, reverse polarity protection PoE: 802.3af, Type 1, Class 3 |
| Power Consumption and Current | With extra load: 12 VDC, 0.55 A, max. 6.5 W PoE (802.3af, 36 V to 57 V), 0.20 A to 0.15 A, max. 7.5 W, Class 3 |
| Power Interface | Ø5.5 mm coaxial power plug |
| Camera Material | Aluminum alloy body |
| Camera Dimension | Ø121 × 92 mm (Ø4.8" × 3.6") |
| Package Dimension | 150 × 150 × 141 mm (5.9" × 5.9" × 5.6") |
| Camera Weight | 590 g (1.3 lb.) |
| With Package Weight | 826 g (1.8 lb.) |
| Approval | |
| EMC | FCC SDoC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2019, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC VoC (ICES-003: Issue 6, 2019); KC (KN 32: 2015, KN 35: 2015) |
| Safety | UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014); CE-LVD (EN 60950-1:2006+A2:2013, IEC 62368-1:2014+A11:2017); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015); LOA (SANS IEC60950-1) |
| Environment | CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006) |
| Protection | Ingress protection: IP67 (IEC 60529-2013), IK10 (IEC 62262:2002) |

▪ Available Model

DS-2CD3126G2-IS (2.8/4/6 mm)

▪ Dimension



▪ Accessory

▪ Optional

| DS-1276ZJ-SUS Corner Mount | DS-1280ZJ-DM46 Junction Box | DS-1272ZJ-120B Wall Mount | DS-1275ZJ-SUS Vertical Pole Mount |
|-------------------------------|--------------------------------|------------------------------|--------------------------------------|
| | | | |
| | | | |

| DS-1272ZJ-120 Wall Mount | DS-1253ZJ-M Rain Shade | DS-1271ZJ-120 Pendant Mount |
|---|---|---|
|  |  |  |
|  |  |  |

Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5888
www.seasales@ Hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@ Hikvision.com

Hikvision Australia
T +61-2-8590-6233
salesau@ Hikvision.com

Hikvision India
T +91-22-28489900
sales@primarikhikvision.com

Hikvision Canada
T +1-866-200-6890
sales.canada@ Hikvision.com

Hikvision Thailand
T +662-275-9999
sales.thailand@ Hikvision.com

Hikvision Europe
T +33-23-5542770
sales.eu@ Hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@ Hikvision.com

Hikvision Brazil
T +55 11 3388-0050
Latam.support@ Hikvision.com

Hikvision Turkey
T +90 (216)521-7070-7074
sales.tr@ Hikvision.com

Hikvision Malaysia
T +601-7852-2413
sales.my@ Hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@ Hikvision.com

Hikvision South Africa
Tel: +27 (11) 0361172
sales_sfrica@ Hikvision.com

Hikvision France
T +33(0)1-85-330-460
info.fr@ Hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikita.pantilov@ Hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vi@ Hikvision.com

Hikvision UAE
T +971-4-442090
salesme@ Hikvision.com

Hikvision Singapore
T +65-6884-4718
sg@ Hikvision.com

Hikvision Spain
T +34-91-737-16-50
info.es@ Hikvision.com

Hikvision Tashkent
T +99-97-1238-8438
uzb@ Hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@ Hikvision.com

Hikvision Russia
T +7-495-069-67-89
salesr@ Hikvision.com

Hikvision Korea
T +82-031-731-8817
sales.korea@ Hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@ Hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@ Hikvision.com

Hikvision Colombia
sales.colombia@ Hikvision.com