

DS-K1T642E Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- Face recognition distance: 0.3 m to 3 m
- Max. 6000 faces capacity, Max.10,000 cards, and Max. 150,000 event capacity
- Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%
- Two-way audio with indoor station and main station
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Remotely opens door and starts live view via Hik-Connect
- Supports ISAPI and ISUP5.0 protocol
- Configuration via the web client





Specification

Type IPS Operation method Cap Video Pixel 2 N Lens × 2 Audio Tone quality No Network Communication protocol ISL	oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI D M/100 M/1000 M self-adaptive
Type IPS Operation method Cap Video Pixel 2 N Lens × 2 Audio Tone quality No Network Communication protocol ISL Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	S Full Screen apacitive touch screen MP 2 oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI 0 M/100 M/1000 M self-adaptive
Operation method Video Pixel 2 N Lens × 2 Audio Tone quality No Network Communication protocol ISU Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	MP 2 oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI D M/100 M/1000 M self-adaptive
Video Pixel 2 N Lens × 2 Audio Tone quality No Network Communication protocol ISL Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	MP 2 oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI 0 M/100 M/1000 M self-adaptive
Pixel 2 N Lens × 2 Audio Tone quality No Network Communication protocol ISU Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI O M/100 M/1000 M self-adaptive
Lens × 2 Audio Tone quality No Network Communication protocol ISL Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI O M/100 M/1000 M self-adaptive
Audio Tone quality No Network Communication protocol Wired network Interface Network interface Lock output Exit button Interface 1	oise suppression and echo cancellation UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI D M/100 M/1000 M self-adaptive
Tone quality No Network Communication protocol Wired network 10 Interface Network interface Lock output Exit button No ISU ISU III III III III III II	UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI O M/100 M/1000 M self-adaptive
Network Communication protocol ISU Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	UP 5.0, ISAPI, NetSDK, HikCentral Pro OpenAPI, and Hik-ProConnect OpenAPI D M/100 M/1000 M self-adaptive
Communication protocol ISU Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	0 M/100 M/1000 M self-adaptive
Wired network 10 Interface Network interface 1 Lock output 1 Exit button 1	0 M/100 M/1000 M self-adaptive
InterfaceNetwork interface1Lock output1Exit button1	
Network interface1Lock output1Exit button1	
Lock output 1 Exit button 1	
Exit button 1	
Door contact input 1	
	•
Power interface 2-p	pin
Capacity	
' '	000
Card capacity 10,	0,000
· ·	50,000
Authentication	
Face recognition distance 0.3	3 to 3 m
Face recognition accuracy rate > 9	99%
Face recognition duration <	0.2 s
Card type EN	M card
Card reading frequency 125	25 KHz
Function	
QR code recognition Sup	upport
Face anti-spoofing Sup	upport
Audio prompt Sup	upport
Time synchronization Sup	upport
General	
Power supply method 12	2V/2A (power adapter not included)
Working temperature -10	0 °C to 50 °C (14 °F to 122 °F)
Working humidity 0 to	to 90% (No condensing)
Dimensions 118	18 mm × 118 mm × 20 mm (4.6" × 4.6" × 0.7")
Application environment Ind	door
Installation Sur	urface, optional base stand
language	nglish, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, ortuguese (Brazil)



Platform


Hik-ProConnect and HikCentral Professional

Available Model

DS-K1T642E

Dimension









Distributed by

HIKVISION'

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 [216]521 7070- 7074 sales,tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 [10] 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T+971-4-4432090 salesme@hikvision.com

Hikvision Singapore T+65-6684-4718 sg@hikvision.com

Hlkvision Spain T+34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 into.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com